



IR CARBON SULPHUR ANALYZER BANA-403

IR CARBON SULPHUR ANALYZER BANA-403

IR Carbon Sulfur Analyzer is developed for the accurate and safe analysis of carbon and sulfur in inorganic samples. It can rapidly and accurately conduct content determination of carbon and sulfur in materials like steel, iron, alloy, nonferrous metals, etc. This is a high-tech product that integrates optical, electrical, computer, and analytical technology into one.

Used in Mining, Construction Material, Food, Geology, Commercial Inspection, Automotive, Aviation, Steel Products, Minerals, Non-Ferrous Metals, Non-Ferrous Metal Alloys, Inorganic Materials, Research.

Also known as Laboratory IR Carbon Sulfur Analyzer.

BANA-403 IR CARBON SULPHUR ANALYZER



Advanced User-Friendly interface.

Automatic Diagnosis System

Linearization calibration technology.

Long MTBM (Mean Time Between Maintenance)

Quick and efficient procedure reduces the cycle time and enables the user to enjoy a stress free operation environment.

High Throughput.

Whole machine adopts modular design, highly integrated electronics circuits.

Fully automatic cleaning system with noiseless and vacuum-free dust removal.

Fast and easy maintenance.

SPECIFICATIONS

Model	BANA-403
Carbon Measurement Range	0.00001% - 99.99999%
Sulphur Measurement Range	0.00001% - 99.99999%
Carbon Analysis Precision	RSD \leq 0.5%
Sulphur Analysis Precision	RSD \leq 1%
Carbon Detection Point	C Pond (can add low C Pond)
Sulphur Detection Point	S Pond (can add low S Pond)
Carrier Gas	Oxygen: Purity \geq 99.5% , Pressure: 0.18 MPa \pm 5%
Operation Gas	Oxygen: Purity \geq 99.5% , Pressure: 0.18 MPa \pm 5%
Time of analysis	20 to 60 seconds adjustable (Usually 35 seconds)
Sensitivity (The minimum readings)	C/s 0.1 ppm
Dimension	540x600x800 mm
Weight	80 kg
Sample weight	0.5 g
Power Supply	AC 220 V \pm 5%, 50 Hz \pm 2%



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com