



AUTO CHEMISTRY ANALYZER BANA-803

AUTO CHEMISTRY ANALYZER BANA-803

Auto Chemistry Analyzer used to measure different chemicals and clinical chemistry of human biological samples. Used in Research, Hospital, Clinical chemistry, Laboratory, Pharmaceutical.
Also known as Routine biochemistry analysers.

BANA-803 AUTO CHEMISTRY ANALYZER



60 Sample positions (90 sample positions optional)
90 Reagent positions.
120 Reaction cuvettes.
400 Tests per hour.
Probe with anti-collision function, liquid level detection function.
Built-in sample barcode system optional

SPECIFICATIONS

Model	BANA-803
Overall Performance	
Throughput	400 Tests/hour
Analysis Method	End-point, Fixed-time, Rate(Kinetic)
Certificates	CE, FDA, ISO9001, ISO13485
Sample & Reagent System	
Sample Positions	60 or 90 sample positions, built-in barcode system available
Reagent Positions	90 refrigerated reagent positions
Sample Volume	1~70 μ l
Reagent Volume	10~350 μ l
Probe	Teflon coating, with anti-collision function, liquid level detection function
Probe Washing	Automatic washing interior and exterior
Reagent Cooling	2~8 $^{\circ}$ C
Reaction System	
Temperature Control	37 \pm 0.1 $^{\circ}$ C, real-time monitoring
Cuvettes	120 reusable cuvettes, optical length 6mm
Mixer Probe	Independent stirring
Washing	Automatic cuvettes washing
STAT Function	YES
Optical System	
Light Source	12 V/30 W halogen-tungsten lamp
Spectrophotometry	Post-spectral spectrophotometry
Wavelength	340, 405, 450, 480, 505, 546, 570, 600, 630, 700, 750, 800 nm
Absorbance	0~3.5Abs
Calibration & QC	
Calibration	Linear: K factor, 1-point, 2-point and multipoint linear Non-Linear: Spline, Polygon, Index, Ogarithm, Logit-4P, Logit-5P

Quality Control	Real-time QC, Westgard multi rule, Cumulative Sum Check, Twin Plot(2D)
Data Management	
Software	Windows 7/8/10, 32 or 64 bit
LIS System	Bi-direction, support HL7 protocol
Interface	TCP/IP Network interface
Printer	External, multiple reporting mode available
Working Conditions	
Power Supply	220 V±10% 50/60 HZ, 110 V±10% 60 Hz, 500 VA
Temperature	15~30°C
Water Consumption	Deionized water:10 L/h
Humidity	40%~85%
Size & Weight	
External Size (W*D*H)	1170x775x1145 mm
Net Weight	190 kg
Package Size (W*D*H)	1348x928x1377 mm
Gross Weight	257 kg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com