



PRE AND POST VACUUM CLASS B AUTOCLAVE BAPV-202

PRE AND POST VACUUM CLASS B AUTOCLAVE BAPV-202

Reliable and robust class B autoclaves intended to deliver highest quality of sterilization. These autoclaves are easy to clean and its compact dimensions make it an ideal option for today's contemporary clinic.

Used in Medical, Dental, Laboratory, Pharmaceutical, Research.

Also known as Medical Sterilizer, Dental Autoclave, Medical Autoclave, Pre and Post Vacuum Autoclave, Benchtop Autoclave, Benchtop Sterilizer, Benchtop Steam Sterilizer, Laboratory Medical Autoclave.

BAPV-202 PRE AND POST VACUUM CLASS B AUTOCLAVE



- Pre and Post Vacuum Sterilizer
- Dual core control system
- 11 Preset Sterilization Cycles
- Maximum negative pressure of -0.80 bar
- Preheated chamber keeps the chamber warm and ready to use
- LCD display
- High density bacteria filter
- User-defined cycles and cleaning programs
- Drying time: 1-60 min
- Printer: Thermal/Stylus
- Interface: RS232
- ISO & CE 1366 Certified
- Vacuum Helix and Bowie & Dick Test passed
- Powerful steam generator and vacuum pump
- First class safety system with electrical lock
- Multi languages available: English, Italian, German, Chinese
- Separate and set up and service menu
- Password protection
- Safety features: Over heat control, over pressure control, safety door locking system, low water level indicator
- Chamber Material: Stainless Steel 304
- Safety valvex1, Handle for tray holderx1, Tray holderx1

SPECIFICATIONS

Model	BAPV-202
Capacity	12 L
Sterilization Temperature	121°C, 134°C
Sterilization Time	4 min - 60 min
Times of Sterilization after filled up	4 - 5 times
Working Pressure	0.21 - 0.23 MPa
Maximum Working Pressure	0.21 - 0.23 Mpa
Pressure Sensor	Yes
Precision of Pressure Sensor	0.1 KPA
Precision of Temperature Sensor	0.1°C
Maximum Vacuum in Bar	0.82
Water supply system	Manual
Quantity of clean water tank	1

Quantity of waste water tank	1
Water Tank	2 x 4.5L Internal Stainless Steel water tanks
Quantity of steam generator	1
Water Filter	1
Vapour Filter	Yes
Temperature Sensor	Yes
Automatic protection when overpressure	Yes
Automatic protection when over temperature	Yes
Bacteria Filter	1
Fuse	2
Power Cable	1
USB output	yes
Lock system of door	Mechanic + Electrical lockers
Screen size	6 X 4.25 cm
Life span	5 years
Hot air exhaust system	Copper condenser, fan
121°C Solid	Yes
121°C Porous	Yes
121°C Hollow	Yes
134°C Solid	Yes
134°C Porous	Yes
134°C Hollow	Yes
B&D Test	Yes
Helix Test	Yes
Vacuum Test	Yes
Clean Program	Yes
Prion Program	Yes
User Define	Yes
Chamber Dimension	200x360 mm
Diameter of chamber	200 mm
Depth of chamber	360 mm
Overall Dimension (LxWxH)	660x445x390 mm
Packing Size	820 x 560 x 550 mm
Minimum size of table for installation	54 x 41.5 mm
Sterilization programs	Yes/No
Weight	59/70 kg
Power	2400 W
Power Supply	220 V, 50Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Unit
1700606006	Ring	1
1700606007	Inner temperature sensor	1
1700606008	pt1000	1
1700606009	pt1000 (packing with plastic)	1
1700606010	Heating circle	1

Accessory Code	Name	Unit
1700606019	Three-way solenoid valve	2
1700606020	Germ-tight filter	1
1700606021	Voltage transformer	1
1700606022	switch	1
1700606023	Bleeder valve	2

1700606011	Steam generator cover	1Set
1700606012	Steam generator stand	1Set
1700606013	Steam generator spring type gasket	1
1700606014	Heating Rod	3
1700606015	Water Pump	1
1700606016	Vacuum Pump	1
1700606017	Fuse Wire	2
1700606018	Normally closed solenoid valve	3

1700606024	Fan	1
1700606025	Printer	1
1700606026	Control panel	1set
1700606027	LED	1set
1700606028	Big Pipe	1Kg
1700606029	Small Pipe	1kg
1700606030	Liquid sensor	3
1700606031	Electromagnet	1



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
 Email: contact@biolabscientific.com | Website: www.biolabscientific.com