



BLOOD BANK REFRIGERATOR BBBF-302

BLOOD BANK REFRIGERATOR BBBF-302

Blood bank refrigerator designed to meet the storage requirement of whole blood and blood components. Maintains optimal temperature range $4\pm 1^{\circ}\text{C}$ required and capacity ranges from 88 L to 1380 L. Microprocessor controller is provided for display of temperature along with alarm systems.

Used in Immunohematology Department, Blood Bank, Laboratory, Research, Medical, Pharmaceutical.

Also known as Laboratory Blood Bank Refrigerator.

BBBF-302 BLOOD BANK REFRIGERATOR



Microprocessor controlled forced-air cooling with electrical heat compensation system

Digital temperature display for upper and lower sections in chamber with 0.1°C resolution

Consistent cabinet temperature $2-6^{\circ}\text{C}$

High-tech integrated sensors to display and control temperature

Auto-defrost to remove moisture on cooling surface

Build-in backup battery to display temperature and to operate audible and visual alarm systems for up to 72 hours without ac power

Equipped with a complete temperature alarm system featuring audible buzzer and visible flashing light

Standard with laser printer

Standard with acrylic inner small door, for less affection on other room when one door open

Safety lock to prevent unauthorized access

Storage space designed for easy sorting of a variety of blood products

SPECIFICATIONS

Model	BBBF-302
Capacity	208 L
Temperature Range	$4^{\circ}\text{C}\pm 1$
Ambient Temperature	$10\sim 32^{\circ}\text{C}$
Bloodbags (450ml)	132
Refrigerant	R134a
Defrost Method	Auto Defrost
Controller	Microprocessor Control with digital Display
Control Sensor	NTC
Cooling Type	Forced air cooling
Compressor brand/QTY	EMBRACO/1
Shelf/drawer	Shelves/4
Alarms	High/low temperature, Power off, Temperature controller malfunction, Backup battery malfunction, Ambient temperature $10\sim 32^{\circ}\text{C}$, Power failure backup system(alarm) 8h
Insulation	PURF
Material Inside	Stainless steel
Material Outside	Color sprayed steel
Noise Level	51.2 dB
Internal Size	432x462x478 mm
External Size	540x640x1530 mm
Package Size	590x700x1700 mm

CBM	0.7
20GP/40GP/40HQ	27/60/60
NT./GT. (kg)	96/120kg
Power consumption (kW.h/24h)	2.22
Power	183 W
Current (A)	0.8A
Standard Accessories	Caster, 1 Outer Door, Heating & Foam Glass Door, 4 Inner Door, 1/25mm Test Hole, Thermal Printer, LED Light
Optional Accessory	Temperature recorder Datalogger



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
 Email: contact@biolabscientific.com | Website: www.biolabscientific.com