



BENCHTOP SPECTROPHOTOMETER BBSP-803

BENCHTOP SPECTROPHOTOMETER BBSP-803

Benchtop Spectrophotometer is used for measuring the color and appearance of fluorescent, opaque, transparent and translucent samples under various illuminants

BBSP-803 BENCHTOP SPECTROPHOTOMETER

Double Array 256 Image Element CMOS Sensor; Long life-span stable LED UV LED.

With reflective and transmissive spectrum, accurate Lab value, good to calculate color formula and do precise color transmission.

Auto identify measuring aperture. Freely switchable between 3 measuring apertures: Φ 25.4mm/8mm/4mm. Users also can customize apertures.

Built-in temperature sensor to monitor and compensate the measuring temperature to ensure the measurement more precision.

Wavelength range 360nm - 780nm. Built-in 400nm/420nm/460nm cut off Xenon lamp, more professional in UV measurement.

Independent light source detector, continuously monitor the condition of light sources to ensure the light source reliable.

Multiple measurement modes: Quality Management Mode, Sample Mode; Meet more users' requirement.

More powerful extended functions at the PC software.

SPECIFICATIONS

Model	BBSP-803
Illuminant	360nm-780nm Combined LED Lamp, 400nm cut-off, 420nm cut-off, UV Lamp
Sensor	256 Image Element Double Array CMOS Image Sensor
Wavelength Pitch	10 nm
Semiband Width	10 nm
Reflectance Range	0-200%
Measuring Aperture	Reflective : Φ 30mm/ Φ 25.4mm, Φ 18mm/ Φ 15mm, Φ 10mm/ Φ 8mm, Φ 6mm/ Φ 4mm; Transmissive : Φ 30mm, Φ 25.4mm;
Integrating Sphere Size	Φ 154mm
Optical Geometry	Reflectance: d/8 (SCI&SCE; Include UV/Exclude UV) Transmittance: d/0 (SCI&SCE; Include UV/Exclude UV) Conforms to CIE No.15, GB/T 3978, GB 2893, GB/T 18833, ISO7724/1, ASTM E1164, DIN5033 Teil7
Specular Component	Reflectance: SCI&SCE / Transmittance: SCI&SCE
Color Space	CIE LAB,XYZ,Yxy,LCh,CIE LUV,Musell,s-RGB,HunterLab, β xy,DIN Lab99
Color Difference Formula	ΔE_{ab} , ΔE_{uv} , ΔE_{94} , $\Delta E_{cmc}(2:1)$, $\Delta E_{cmc}(1:1)$, ΔE_{00} , DIN ΔE_{99} , ΔE_{Hunter}
Colorimetric Index	WI (ASTM E313, CIE/ISO, AATCC, Hunter), YI (ASTM D1925, ASTM 313), MI (Metamerism Index), Staining Fastness, Color Fastness, Color Strength, Opacity, 8° Glossiness, Gardner Index, APHA/Pt-Co Index, 555 Index
Observer	2° / 10°
Illuminants	D65,A,C,D50,D55,D75,F1,F2,F3,F4,F5,F6,F7,F8,F9,F10,F11,F12
Displayed Data	Spectrogram/Values, Chromaticity Values, Color Difference Values/Graph, Pass/Fail Result, Color Offset
Measurement time	About 2.4s (Measure SCI & SCE about 5s)
Repeatability	Spectral reflectance: Φ 25.4mm/SCI, Standard deviation within 0.05% (400 nm to 700 nm: within 0.04%) Chromaticity value: Φ 25.4mm/SCI, Standard deviation within ΔE^*_{ab} 0.01 Spectral Transmittance: Φ 25.4mm/SCI, Standard deviation within 0.05% (400 nm to 700 nm: within 0.04%) Chromaticity value: Φ 25.4mm/SCI, Standard deviation within ΔE^*_{ab} 0.02
Inter-instrument Error	Φ 25.4mm/SCI, Within ΔE^*_{ab} 0.15 (Average for 12 BCRA Series II color tiles)
Working Environment	Temperature: 0~40°C; Humidity: 0~85% (No Condensation)

Storage Environment	Temperature: -20~50°C; Humidity: 0~85% (No Condensation)
Language	English and Chinese
Data Storage capacity	Standard 5000 Pcs, Sample 40000 Pcs (one PCS can include both SCI and SCE)
Light Source Device Life	5 years, more than 3 million times measurements.
Screen	7" TFT Capacitive Screen-touch Display
Data Port	USB & Bluetooth
Standard Accessory	White and Black Calibration Board, Checking Green Board, Sample Holder, $\Phi 4$ mm, $\Phi 8$ mm, $\Phi 15$ mm, $\Phi 25.4$ mm Aperture, Power Adapter, USB Cable, User Guide, PC Software Transmissive Test Clamp Component
Optional Accessory	Micro-printer
Size	370x300x200 mm
Weight	9.6kg
Power Supply	DC 24V, 3A Power Adapter



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com