



## BENCHTOP HIGH SPEED CENTRIFUGE BCBH-402

## BENCHTOP HIGH SPEED CENTRIFUGE BCBH-402

Designed around your applications to provide you competent sample processing and reliable results. Microcomputer programmable with excellent temperature controls and low noise operation maximize your productivity. Highly efficient with low maintenance requirements, it is an ideal separation tool for multiple research applications.

### BCBH-402 BENCHTOP HIGH SPEED CENTRIFUGE

Brushless frequency motor, in great torque, free maintenance, no powder pollution, quick in speed up and down

Microprocessor control

Digital display in time, speed and RCF

10 kinds of accelerating and decelerating speed for your choice

Automatically electric lid lock, over speed, over temperature protection and imbalance protection

High quality steel centrifuge body, stainless steel chamber, 3 tiers protection, safe and reliable

Rotor is connected to spindle by specialized taper sleeve, loading simple and quick, no direction

## SPECIFICATIONS

Model	BCBH-402
Maximum Capacity (No of tubes x Vol.)	6 x 100 ml
Maximum Speed	18500 rpm
Speed Accuracy	$\pm 20$ r / min
Maximum RCF	$23990 \times g$
Time Range	0 ~ 99 min
Acc / Dec	10 Kinds
Noise Level	$\leq 65$ dB(A)
Certificates	CE, ISO & Calibration report are available
RPM / RCF Convert	Yes
Overall Dimension	513 × 370 × 320 mm
Net. Weight	42 kg
Power Supply	AC 220 V / 110 V 50 HZ / 60 HZ



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)