



BENCHTOP LOW SPEED CENTRIFUGE BCBL-304

BENCHTOP LOW SPEED CENTRIFUGE BCBL-304

Designed around your applications to provide you competent sample processing and reliable results. Microcomputer programmable with excellent temperature controls and low noise operation maximize your productivity. Highly efficient with low maintenance requirements, it is an ideal separation tool for multiple research applications.

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Benchtop Centrifuge, Non Refrigerated High Speed Centrifuge, Laboratory Tabletop Centrifuge.

BCBL-304 BENCHTOP LOW SPEED CENTRIFUGE



3 layers protection of steel structure and with the stainless steel chamber.

Advance CPU control system.

Brushless DC frequency motor with simpler construction, more reliable performance, longer life.

Electric lid lock, compact design, super speed and imbalance protection.

Emergency lock under the bottom of the centrifuge which help you open the lid when power off.

SPECIFICATIONS

Model	BCBL-304
Maximum Capacity (No of tubes x Vol.)	4x100 ml
Maximum Speed	4000 rpm
Speed Accuracy	±20 rpm
Maximum RCF	2610xg
Time Range	0~99 min
Overall Dimension	528x370x280 mm
Noise Level	<55 dB(A)
Net. Weight	28 kg
Power Supply	AC 220 V 50 Hz 2A
Package	Wooden box

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	RPM	RCF _{xg}
2301614006	Swing out rotor	4x50 ml/100 ml	4000	2250xg
2301614007	Swing out rotor	16x15 ml	4000	2150xg
2301614008	Swing out rotor	24x10 ml	4000	2220xg
2301614009	Angle rotor	18x10 ml	4000	2250xg
2301614010	Angle rotor	24x15 ml	4000	2270xg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com