



BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE BCBLR-401

BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE

BCBLR-401

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

BCBLR-401 BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE

Widely used for laboratory, chemistry and hospital
10 kinds of acceleration and deceleration
More than 10 rotors for your choice
High speed, low noise, compact design and small vibration
User-friendly LED display provides speed, time and temperature parameters
Brushless frequency motor which in great torque, no powder pollution, free maintenance, quick in speed up and down
Imbalance sensor and over speed sensor, the centrifuge body is made of high-quality steel, very safe

SPECIFICATIONS

Model	BCBLR-401
Maximum Capacity (No of tubes x Vol.)	4 x 180 ml
Maximum Speed	18500 rpm
Speed Accuracy	± 20 r / min
Maximum RCF	23990 × g
Time Range	0 ~ 99 min
Acc / Dec	10 Kinds
Noise Level	≤ 55 dBA
Certificates	CE,ISO & Calibration report are available
RPM / RCF Convert	Yes
Net. Weight	35 kg
Power Supply	AC 220 V /110 V 50 HZ / 60 HZ



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com