



# BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE BCBLR-402

# BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE BCBLR-402

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

## BCBLR-402 BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE

Refrigerated centrifuge  
Widely used for laboratory, chemistry and hospital  
Pre-cooling design, 10 kinds of acceleration and deceleration  
More than 10 rotors for your choice  
High speed, low noise, compact design and small vibration  
User-friendly LED display provides speed, time and temperature parameters  
Brushless frequency motor which in great torque, no powder pollution, free maintenance, quick in speed up and down  
Imbalance sensor and over speed sensor, the centrifuge body is made of high-quality steel, very safe

## SPECIFICATIONS

Model	BCBLR-402
Maximum Capacity (No of tubes x Vol.)	4 x 180 ml
Maximum Speed	18500 rpm
Speed Accuracy	± 20 r / min
Maximum RCF	23990 × g
Time Range	0 ~ 99 h 59 min
Acc / Dec	10 Kinds
Noise Level	≤ 55 dBA
Certificates	CE, ISO & Calibration report are available
RPM / RCF Convert	Yes
Temperature	- 20 ~ 40 °C
Net. Weight	110 kg
Temperature Accuracy	± 1 °C
Power Supply	AC 220 V / 110 V 50 HZ / 60 HZ



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)