



BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE BCBLR-404

BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE

BCBLR-404

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

BCBLR-404 BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE

Brushless frequency motor, in great torque, free maintenance, no powder pollution, quick in speed up and down

Imported compressors fluorine free, double cycle cooling, cold and hot alternating easily, free environment pollution and precise in temperature control

Microprocessor control, digital display which indicates the speed, time, RCF in operation, speed raising and reducing quickly, operate simply

Running parameter can be edited

10 kinds of accelerating and decelerating speed for your choice

Automatically electric lid lock, super speed, over temperature protection and imbalance protection

The centrifuge body is made of high quality steel, safe and reliable

Rotor is connected to spindle by specialized taper sleeve, loading simple and quick, no direction

There are several kinds of rotors for your choice, adapters can be designed by experimental requirements

3 tiers protection steel cover and get the ideal centrifugation result

SPECIFICATIONS

Model	BCBLR-404
Maximum Capacity (No of tubes x Vol.)	6 x 100 ml
Maximum Speed	6000 rpm
Speed Accuracy	± 20 r / min
Maximum RCF	3660 × g
Time Range	1 ~ 99 min 59 sec
Temperature Accuracy	± 1° C
Noise Level	≤58 dBA
Temperature	- 20 °C ~ 40 °C
Net. Weight	48 kg
Overall Dimension	520 x 520 x 285 mm
Power Supply	220 V, 50 Hz / 60 Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com