



BENCHTOP LOW SPEED CENTRIFUGE BCBLR-405

BENCHTOP LOW SPEED CENTRIFUGE BCBLR-405

Designed around your applications to provide you competent sample processing and reliable results. Microcomputer programmable with excellent temperature controls and low noise operation maximize your productivity. Highly efficient with low maintenance requirements, it is an ideal separation tool for multiple research applications.

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Benchtop Centrifuge, Non Refrigerated High Speed Centrifuge, Laboratory Tabletop Centrifuge.

BCBLR-405 BENCHTOP LOW SPEED CENTRIFUGE

Frequency conversion motor with simpler construction, more reliable performance, longer life and quietly running

Automatically electric lid lock, super speed, over temperature protection and imbalance protection

Rotor is connected to spindle by specialized taper sleeve, loading simple and quick, no direction, safe and reliable

Microprocessor control, digital display in the speed, time, RCF in operation, speed raising and reducing quick, operate simply

High quality steel body, stainless chamber makes sure the safety of instrument and people

SPECIFICATIONS

Model	BCBLR-405
Maximum Capacity (No of tubes x Vol.)	4 x 20 ml (PRP tube/ kit, brand such as DR.PRP 20 ml, Yes/BS prp, 3E prp etc.)
Maximum Speed	4000 rpm
Speed Accuracy	± 20 r / min
Maximum RCF	2820 × g
Time Range	0 ~ 99 min
Acc / Dec	10 Kinds
Noise Level	≤ 55 dBA
Certificates	CE, ISO & Calibration report are available
RPM / RCF Convert	Yes
Overall Dimension	540 x 370 x 280 mm
Net. Weight	32 kg
Power Supply	AC 220 V / 110 V 50 HZ / 60 HZ



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com