

PRODUCT CATALOG



BIOLOGICAL SAFETY CABINET CLASS II BCBS-403





BIOLOGICAL SAFETY CABINET CLASS II BCBS-403

Biolab Biological Safety Cabinet Class II Series is engineered specifically for laboratory operations that require user and product protection. Operates with a negative air pressure for personnel protection and HEPA filtered laminar airflow for product protection. Suitable for microbiological and research applications that do not involve radioactive substances and toxic contaminants.

Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory. Also known as Class II BSC, Biosafety Cabinet.

BCBS-403 BIOLOGICAL SAFETY CABINET CLASS II



Time reserve function

Stainless Steel 304 table for operation

Digital VFD display for easy monitoring of all parameters

Emission of 253.7 nm for highly efficient decontamination

Two-layered marinated toughened glass (25mm) motorized front window

Negative air pressure provides personnel protection by constant movement of air in working area

Remote control operation including front sash movement and fan speed control

Motored front window with timer function

Intrinsic sterilization is achieved after activating cabinet for 30 min via UV timing

Filter Life Indicator: Pressure value displayed to show life utility of main filter

Foot switch to adjust the height of the front window

Low noise and high energy efficiency for operational cost savings

Audio and visual alarm for filter replacement, front window over height and abnormal airflow

SPECIFICATIONS

Model	BCBS-403	
Туре	Class II, Type B2	
Filter	ULPA Filter - Two, 99.9995% efficiency at 0.12 μm, filter life indicator	
Inflow Velocity	0.53±0.025 m/s	
Down Flow Velocity	0.33±0.025 m/s	
UV Lamp	30Wx1 UV timer, UV life indicator, emission of 235.7 nanometers for most efficient decontamination	
LED Lamp	12Wx2	
Illumination	≥1000 lux	
Waterproof Socket	Two, total load of sockets: 500W	
Work Surface Height	750 mm (Size can be customized according to requirements)	
Tested Opening	Safety height 200 mm (8")	
Max Opening	440 mm	
Front Window	Motorized, two layer laminated toughened glass ≥ 6 mm, Anti UV	
Airflow System	0% air recirculation, 100% air exhaust	
Control System	Microprocessor	
Caster	Footmaster Caster	
Display	LCD Display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.	
Work Zone Material	304 Stainless steel	
Main Body Material	Cold roller steel with anti bacteria powder coating	

Visual and Audio Alarm	Abnormal airflow velocity, filter replacement, front window at unsafe height, high filter pressure alarm, abnormal power failure	
Standard Accessory	LED lamp 2pcs, UV lamp 1 pc, Base stand Remote control, Foot switch, Drain valve, Waterproof Socket 2 pcs, Exhaust blower, Exhaust duct	
Optional Accessory	Water and Gas tap, Electric Height adjustable base stand, Armrest	
Noise	≤65dB	
Internal Size (WxDxH)	940x600x660 mm	
External Size (WxDxH)	1100x755x2250 mm	
Package Size (WxDxH)	1230x1060x1840 mm (main body) 930x800x700 mm (Exhaust blower)	
Gross Weight	243 kg ; 52 kg	
Consumption	1300 W	
Power Supply	AC220V 50/60Hz ; 110 60Hz	

ACCESSORIES

Accessory Code	Name
6000606013	UV Lampx2

OPTIONAL ACCESSORIES

Accessory Code	Name	External Dimension	Package Size (mm)
2200606006	Infrared Sterilizer	150x95x210 mm	
2200606007	Airflow Tester		
2200606008	Formalin Fumigation Sterilizer		300x200x160 mm
2200606009	Ammonium Hydrogen Carbonate Neutralizer		300x200x160 mm
2200606010	Armrest		
2200606011	Laboratory Chair		
2200606012	Dust Particle Counter		
2200606013	Digital Sound Level Meter		
2200606014	Illumination Meter		
2200606015	Air Flow Anemometer		
2200606016	Protective Garment		
2200606017	Protective Gloves		



Biolab Scientific Ltd.