



BIOLOGICAL SAFETY CABINET CLASS II BCBS-702

BIOLOGICAL SAFETY CABINET CLASS II BCBS-702

Biolab Biological Safety Cabinet Class II Series is engineered specifically for laboratory operations that require user and product protection. Operates with a negative air pressure for personnel protection and HEPA filtered laminar airflow for product protection. Suitable for microbiological and research applications that do not involve radioactive substances and toxic contaminants.

Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory.
Also known as Class II BSC, Biosafety Cabinet.

BCBS-702 BIOLOGICAL SAFETY CABINET CLASS II



- Motorized front window
- Large LCD display, all information displayed
- Automatic air speed adjustable with filter block
- With memory function in case of power-failure
- Side & back wall is made up of single piece stainless steel
- Interlock function: UV lamp and front window; UV lamp and blower, fluorescent lamp; Blower and front window
- Front 10° slanted to offer operator comfort while working for long time, reduce glare and maximize reach into the work area

SPECIFICATIONS

Model	BCBS-702
Type	NSF Certified Class II, Type A2
Airflow Volume (Inflow)	587m ³ /h (346cfm)
Airflow Volume (Down flow)	60%:863m ³ /h (507cfm)
Airflow Volume (Exhaust)	40%:587m ³ /h (346cfm)
Filter	HEPA Filter - Two, 99.995% efficiency at 0.3μm, filter life indicator Filter Guard Type - Aluminum alloy frame , glass filter paper
Max Opening	550 mm (22")
Tested Opening	Safety height 254mm (10")
Work Surface Height	750 mm with optional base stand
Work Zone Material	304 stainless steel
Main Body Material	cold-rolled steel with anti-bacteria power coating
UV Lamp	30 W Germicidal UV lamp, Emission of 253.7 nanometers for most efficient decontamination
LED Lamp	18W x2 LED lamp
Waterproof Socket	2, Total consumption:≤500W
Front Window	Motorized. Two-layer laminated toughened glass ≥5mm. Anti UV
Visual and Audio Alarm	Abnormal airflow velocity; Filter replacement; Front window at unsafe height.
Motor	One ECM motor, 110V& 220V acceptable, Speed adjustable, high efficiency and low power consumption
Noise	NSF 49≤67 dB/EN 12469≤65 dB
Standard Accessory	Illuminating lamp, UV lamp x2, Base stand, SS water x1 & gas tap x1, Drain valve, Waterproof sockets, Stainless Steel I.V. Bar with 10 hooks
Optional Accessory	Armrest, Airflow tester, Formalin fumigation sterilizer, Infrared sterilizer, Electric height adjustable base stand, Remote control

External Size (WxDxH)	1383x775x2295 mm
Internal Size (WxDxH)	1210x600x660 mm
Package Size (WxDxH)	1540x1080x1900 mm
Gross Weight	340 kg
Consumption	500 W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz, Full load Amps: 9A, BTU/Hr: 1689



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com