



CLIMATIC CHAMBER BCCL-202

CLIMATIC CHAMBER BCCL-202

Our chambers provide excellent temperature and lighting control for regulated growth of plants and other products. Its responsive humidification sensor and energy efficient design make it a preferred choice for a wide range of applications.

Used in Supports plant and insect growth, tissue cultivation, antibiotic cultivation and preservation and other controlled temperature experiments..

Also known as Humidity Chamber, Laboratory Climatic Chamber.

BCCL-202 CLIMATIC CHAMBER



Forced convection mode
30 Stages programmable Microcomputer PID
Imported environmental protection insulation materials
Excellent Imported temperature and humidity Sensor
SUS304 stainless steel interior material
ALLCOLDTM: Refrigeration Technology
ALLIGENTTM: Humidification System
ALLFLOWTM: Perfect Air Current Cycling

SPECIFICATIONS

Model	BCCL-202
Capacity	300 L
Temperature Range	10°C~65°C(Light on)/0°C~60°C(Light off)
Temperature Uniformity	±1 (10-40°C)
Temperature Fluctuation	±1°C
Temperature Resolution	0.1°C
Using Environment Temperature	Ambient temp.10~30°C
Using Environment Humidity	<70%
Illumination Range	0-15000 (5 stages adjustable)
Timer Range	0-99h/0-9999mins
Shelves	4
Inner Dimension	1100 x 540 x 520 mm
Overall Dimension	1780 x 770 x 815 mm
Weight (Net/Gross)	183 kg
Power	1350 W



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com