



**FLOOR TYPE HIGH SPEED REFRIGERATED
CENTRIFUGE BCFHR-202**

FLOOR TYPE HIGH SPEED REFRIGERATED CENTRIFUGE

BCFHR-202

Engineered to maximize productivity and reliably deliver a wide range of high speed separations. Stainless steel interiors, integrated refrigeration system and advanced temperature controls make it flexible for your evolving applications. Safety features and low noise operation make it an ideal partner for your day to day separations. Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Floor Type Refrigerated Centrifuge, Benchtop Centrifuge, Laboratory Tabletop Centrifuge.

BCFHR-202 FLOOR TYPE HIGH SPEED REFRIGERATED CENTRIFUGE



Brushless DC frequency motor with simpler construction, more reliable performance, longer life and quietly running

Automatically electric lid lock, super speed, over temperature protection and imbalance protection

The centrifuge body is made of high quality steel, safe and reliable Rotor is connected to spindle by specialized taper sleeve, loading simple and quick, no direction, safe and reliable

Microprocessor control, digital display in the speed, time, RCF in operation, speed raising and reducing quick, operate simply

10 kinds of program stored in the memory, 10 kinds of accelerating and decelerating speed for your choice

3 layers protection of steel structure and get the ideal centrifugation result

It is consistent with CE security certification and ISO9001 quality certification

SPECIFICATIONS

Model	BCFHR-202
Maximum Capacity (No of tubes x Vol.)	4x800 ml
Temperature Range	-20°C to +40°C
Temperature Accuracy	±1°C
Maximum Speed	21000 rpm
Speed Accuracy	±20 rpm
Maximum RCF	28030xg
Time Range	0-23 h 59 min
Overall Dimension	720x540x830 mm
Noise Level	≤60 dB
Net. Weight	170 kg
Power Supply	AC 220V 50HZ 20A
Package	Wooden box

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	RPM	RCF _{xg}
2301206006	Angle rotor	12x1.5/2 ml	21000	28030 _{xg}
2301206007	Angle rotor	24x1.5 ml	17000	26460 _{xg}
2301206008	Angle rotor	16x5 ml	16000	22020 _{xg}
2301206009	Angle rotor	6x30 ml	14000	19060 _{xg}
2301206010	Angle rotor	12x10 ml	15000	22680 _{xg}
2301206011	Angle rotor	12x15 ml	10000	11840 _{xg}
2301206012	Angle rotor	6x10 ml	16000	21500 _{xg}
2301206013	Angle rotor	6x50 ml	12000	16050 _{xg}
2301206014	Angle rotor	8x20 ml	15000	22680 _{xg}
2301206015	Angle rotor	6x70 ml	12000	15570 _{xg}
2301206016	Angle rotor	6x100 ml	12000	16390 _{xg}
2301206017	Vertical rotor	16x5 ml	16000	16450 _{xg}
2301206018	Vertical rotor	8x30 ml	14000	19750 _{xg}
2301206019	Bucket rotor	4x4x96 well	4000	2840 _{xg}
2301206020	Swing rotor	4x800 ml	4000	3450 _{xg}



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com