



GAS CHROMATOGRAPHY BCHR-107

GAS CHROMATOGRAPHY BCHR-107

Chromatography is a technique that enables the separation, identification, and purification of the components of a mixture for qualitative and quantitative analysis. Our extensive range offers variety of products like Gas, Ion and Portable Ion chromatography products to meet all separation needs, including improved resolution, enhanced sensitivity, faster analysis and consistent performance.

Used in Food Testing, Chemical Industry, Beverage Testing, Drug testing, Forensic Science, Pharmaceutical, Molecular Biology, Medical, Research, Laboratory.

Also known as Laboratory Chromatography.

BCHR-107 GAS CHROMATOGRAPHY



PC control, user-friendly interface, and easy to operate.

Heating speed is fast and overshoot temperature is small.

Self-diagnosis, power protection, oven over-temperature protection, and automatic ignition.

It can accurately display the temperature control settings, actual value, and FID amplifier sensitivity.

The single gas system and precise scale pneumatic control valve contribute to excellent reproducibility and stability and can perform analysis of packed column or capillary with wide diameter of 0.53mm.

Packed columns: On-column injection, instantaneous vaporization injection, gas injection.

Open computer system and chromatography workstation can work together to process data.

Large capacity oven facilitates the installation of packed column and capillary.

Built-in heating wire structure.

RS232 communication port.

SPECIFICATIONS

Model	BCHR-107
Column Oven	
Temperature Range	15°C - 399°C above room temperature (increment: 1°C)
Temperature Control Accuracy	Better than $\pm 0.1^\circ\text{C}$ (measured at 200°C)
Hydrogen flame ionization detector (FID)	
Detection limit	$Dt \leq 1 \times 10^{-10}$ g/s (octane and hexadecane)
Baseline drift	$\leq 2 \times 10^{-12}$ A/h
Linear range	$\geq 10^6$
Max. limit temperature	400°C
Other Specifications	
Dimension (LxWxH)	575x480x490 mm
Weight (Kg)	50
Power supply voltage	220 V - ± 22 V 50 Hz ± 0.5 Hz
Power	≤ 1500 W



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com