



## LOW TEMPERATURE CIRCULATOR BCLT-302

## LOW TEMPERATURE CIRCULATOR BCLT-302

We offer you robust circulators equipped with microprocessor controller for high heating and cooling experiments. Fitted with adjustable casters, corrosion resistant interior and exterior, these circulators are a perfect fit for any environment.

Used in Enzyme reactions, Immunoassay, Incubation, Laboratory, Research, Medical, Pharmaceuticals.

Also known as Laboratory water bath.

## BCLT-302 LOW TEMPERATURE CIRCULATOR



- PID controller offers precise temperature control and uniformity
- Corrosion resistant inner and outer chamber made of stainless steel
- Dual LED screen displays temperature and time
- Protection against compressor overload, high/low voltage and current
- Convenient and reliable operation
- Equipped with caster for easy installation

## SPECIFICATIONS

Model	BCLT-302
Capacity	12 L
Temperature Range	-5°C to 100°C
Top Opening	170x110 mm
Inner Dimension (WxDxH)	240x300x200 mm
Outer Dimension (WxDxH)	400x520x800 mm
Power	192 W



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)