



LOW TEMPERATURE CIRCULATOR BCLT-403

LOW TEMPERATURE CIRCULATOR BCLT-403

We offer you robust circulators equipped with microprocessor controller for high heating and cooling experiments. Fitted with adjustable casters, corrosion resistant interior and exterior, these circulators are a perfect fit for any environment.

Used in Enzyme reactions, Immunoassay, Incubation, Laboratory, Research, Medical, Pharmaceuticals.

Also known as Laboratory water bath.

BCLT-403 LOW TEMPERATURE CIRCULATOR



- PID controller offers precise temperature control and uniformity
- Corrosion resistant inner and outer chamber made of stainless steel
- Dual LED screen displays temperature and time
- Protection against compressor overload, high/low voltage and current
- Convenient and reliable operation
- Equipped with caster for easy installation

SPECIFICATIONS

Model	BCLT-403
Capacity	22 L
Temperature Range	-20°C to 100°C
Temperature Resolution	±0.1°C
Top Opening	170x160 mm
Inner Dimension (WxDxH)	355x325x200 mm
Outer Dimension (WxDxH)	450x520x850 mm
Power	260 W



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com