



DRY BATH INCUBATOR BDIB-110

DRY BATH INCUBATOR BDIB-110

Biolab Dry bath incubator features precise temperature control resolution in a compact design to give you reproducible results. This microprocessor controlled device offers you flexibility to accommodate a variety of interchangeable heating blocks for your versatile applications.

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis.

Also known as Laboratory Dry Bath Chiller.

BDIB-110 DRY BATH INCUBATOR



Fast heating speed, uniform heating, accurate temperature control, high stability, low energy consumption and no noise.

Simple or program temperature control mode is available, making the experiment more convenient.

Sliding operation, light touch button, novel and fashionable.

The standard metal blocks are easy to replace, easy to clean and disinfect.

Protect samples from contamination.

The buzzer tone can be turned off, making the experiment quieter.

SPECIFICATIONS

Model	BDIB-110
Temperature Range	RT+5-150°C
Temp. Setting Range	5°C~150°C
Time Range	1min~99h59m (00:00 is continuous)
Block Temp. Stability@40~100°C	±0.5 °C
Block Temp. Stability@>100°C	±1 °C
Block Temp. Uniformity@40°C	±0.3 °C
Block Temp. Uniformity@>40°C	±0.5 °C
Temp. Display Accuracy	0.1 °C
Heating Speed	≤15min(20°C~150°C)
Sample Capacity	2 standard block
Voltage	AC 220V/AC 110V 50Hz/60Hz
Power	400W
Fuse	250V,3A/6A,φ5x20
Dimension	W.285xD.225xH.95
Net Weight(kgs)	2.64 kgs



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com