



-40°C FREEZER CHEST BFRZ-40-401

-40°C FREEZER CHEST BFRZ-40-401

Equipped with precise temperature controls, rugged interiors and safety features, our freezers provide you with the most dependable performance with low maintenance. A perfect partner for your multi cold storage purposes in a contemporary lab set up. Microprocessor based temperature controls provide outstanding temperature uniformity with high quality compressor for energy efficiency.

Used in Routine Cold Storage, Laboratories, Biologicals, Pharmaceuticals, Clinical, Research.

Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

BFRZ-40-401 -40°C FREEZER CHEST



LED digital display and increment at 0.1°C

Permanently lubricated cooling fan for safety and longevity

Independent inner door to avoid more cooling leaking out, and provide more stable inside temperature performance

High density CFC-Free urethane foam insulation

Build-in lock with safety

Lockable caster design

Chemically stable, CFC -free, commercially available and environmentally safe refrigerant

Optimized refrigeration system designed to maximize cooling effect and temperature uniformity

Visible and Audible alarm

Corrosion proof cabinet interior design

Power failure protect: the device would be attack by the high current when all devices restart simultaneously, the start-delay function would protect device from the damage

SPECIFICATIONS

Model	BFRZ-40-401
Capacity	105 L
Temperature Range	-10°C to -40°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	HC-R290
Internal Dimension	480x380x665 mm
Overall Dimension	680x580x935 mm
Package Size	740x680x970 mm
Interior	Stainless steel
Exterior	Color sprayed steel
Controller	Microprocessor, Digital display
Sensor	NTC
Compressor Brand/QTY	CUBIGEL/1
Condenser	Wire tube
Noise Level	50 db
Alarm	High/low temperature, Power off, Sensor malfunction, Temperature controller malfunction

Standard Accessories	Foot, Castor, Test hole 1/25 mm
Weight (Net/Gross)	62/70 kg
Rated Power	120 W
Power Consumption (Kwh/24hrs)	1.65
Rated Current A	1.05
Power Supply	220V, 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com