

# PRODUCT CATALOG



# -25°C UPRIGHT FREEZER BFUR-25-501





### -25°C UPRIGHT FREEZER BFUR-25-501

A perfect partner for your multi cold storage purposes in a contemporary lab set up. Microprocessor based temperature controls provide outstanding temperature uniformity with high quality compressor for energy efficiency. Safety features and durable interiors provide you with the most dependable performance.

Used in Laboratories, Routine Cold Storage, Biologicals, Pharmaceuticals, Clinical, Research.

Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

#### BFUR-25-501 -25°C UPRIGHT FREEZER



Chemically stable, CFC-Free, environmentally, safe refrigerant

High density CFC-Free urethane foam insulation for rigidity and stable storage temperature

Microprocessor control, digital display adjustable

LED digital display

Audible and visible alarm

Controller password protect function to avoid change running parameter randomly Independent inner door to avoid more cooling leaking out, and provide more stable internal temperature performance

Upright side door with built-in handle for easy-opening; limit door hinge to prevent collision when door open

Lockable caster design for customer to move as needed

### **SPECIFICATIONS**

Model	BFUR-25-501
Capacity	268 L
Temperature Range	-10°C to -25°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Refrigerant	R290
Internal Dimension	508x455x1137 mm
Overall Dimension	690x680x1635 mm
Package Size	760x760x1750 mm
Drawers/Shelves	Shelves
Controller	Microprocessor, Digital display
Sensor	NTC
Compressor Brand/QTY	CUBIGELN/1
Noise Level	46 db
Alarm	High/low temperature, Power off, Sensor malfunction, Temperature controller malfunction, Door ajar
Standard Accessories	Caster, Remote alarm
Optional Accessories	Test hole
Power Consumption ( Kwh/24hrs )	3
Power Supply	220V, 50Hz

2



## Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada Email: info@biolabscientific.com | Website: www.biolabscientific.com