



-40°C UPRIGHT FREEZER BFUR-40-306

-40°C UPRIGHT FREEZER BFUR-40-306

Equipped with precise temperature controls, rugged interiors and safety features, our freezers provide you with the most dependable performance with low maintenance. A perfect partner for your multi cold storage purposes in a contemporary lab set up. Microprocessor based temperature controls provide outstanding temperature uniformity with high quality compressor for energy efficiency.

Used in Routine Cold Storage, Laboratories, Biologicals, Pharmaceuticals, Clinical, Research.

Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

BFUR-40-306 -40°C UPRIGHT FREEZER



- LED digital display and increment at 0.1°C
- Permanently lubricated cooling fan for safety and longevity
- Independent inner door to avoid more cooling leaking out, and provide more stable inside temperature performance
- High density CFC-Free urethane foam insulation
- Build-in lock with safety
- Lockable caster design
- Chemically stable, CFC -free, commercially available and environmentally safe refrigerant
- Optimized refrigeration system designed to maximize cooling effect and temperature uniformity
- Visible and Audible alarm
- Corrosion proof cabinet interior design
- Power failure protect: the device would be attack by the high current when all devices restart simultaneously, the start-delay function would protect device from the damage

SPECIFICATIONS

Model	BFUR-40-306
Capacity	936 L
Temperature Range	-25°C to -40°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	Mixed-gas
Internal Dimension	1000x700x1335 mm
Overall Dimension	1304x1000x2017 mm
Package Size	1350x1080x2150 mm
Drawers/Shelves	Shelves
Interior	Stainless steel
Exterior	Color sprayed steel
Controller	Microprocessor, Digital display
Sensor	PTC
Compressor Brand/QTY	SECOP/1
Condenser	Copper tube and finned
Noise Level	50 db

Alarm	High/low temperature, Power failure, Sensor malfunction, Filter screen check, Temperature controller malfunction, Low battery, Condenser clean, High ambient temperature, Door ajar
Standard Accessories	Castor, Inner door, Test hole 1/18 mm, Remote alarm port, USB port
Optional Accessories	USB data logging, Temperature recorder
Weight (Net/Gross)	310/330 kg
Rated Power	1000 W
Power Consumption (Kwh/24hrs)	14.5
Rated Current A	5.8 A
Power Supply	220 V, 50 Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
 Email: contact@biolabscientific.com | Website: www.biolabscientific.com