



HOTPLATE MAGNETIC STIRRER BHMS-105

HOTPLATE MAGNETIC STIRRER BHMS-105

Compact, automatic and powerful hotplate magnetic stirrer has stainless steel material with a ceramic coating which prevents corrosion. It is available with external temperature sensor PT1000, timer, PC control. A warning sign is display when over-temperature. Timer can be set from 1min to 99h 59min. Used with a wide variety of accessories. Used in Cell Culture, Laboratory, Research, Medical.

Also known as Laboratory Magnetic Hotplate Stirrer, Digital Magnetic Stirrer.

BHMS-105 HOTPLATE MAGNETIC STIRRER



Heating temperature up to 280°C

Stainless steel with ceramic coated hotplate resists to corrosion

External temperature sensor PT1000 is available and control accuracy of $\pm 1^\circ\text{C}$, real-time control medium temperature.

LED display temperature and speed.

50°C HOT warning indicates residual hotplate temperature.

ABS casing with fire retardant material, resistance of weak acid and alkali

SPECIFICATIONS

Model	BHMS-105
Capacity	3 L
Stirring Positions	1
Speed Range	100-1500 rpm
Temperature	RT-280°C
Permissible Ambient Temperature	5-40°C
Temperature Increment	1°C
Control Accuracy of Work Plate	$\pm 1 (<100^\circ\text{C})$, $\pm 1\% (>100^\circ\text{C})$
Temperature Accuracy	$\pm 1^\circ\text{C}$
Safety Temperature	320°C
Control Accuracy with Sensor PT1000	$\pm 0.5^\circ\text{C}$
Permissible Relative Humidity	0.8
Heating Warning	50°C
Motor rating Input [W]	5
Motor rating output [W]	3
Heating Output	500 W
Work Plate Size	135 mm
Stirrer Dimension	50 mm
Platform Material	Stainless steel with ceramic coating
Speed Display	LED
Temperature Display	LED
Remote Control (RS232 interface)	No
Motor Type	Brushless DC motor
Protection Class	IP21

Overall Dimension (WxDxH)	150x260x80 mm
Weight	1.8 kg
Power	515 W
Power Supply	100-120V/200-240V, 50/60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com