



COOLED INCUBATOR BICL-403

COOLED INCUBATOR BICL-403

An energy efficient remedy for storing and cooling samples. Absolutely reliable circulation system with PID temperature controller provides optimum storage conditions for your products.

Used in Germination experiments, Biochemical analysis, Cold storage purposes, Incubation, drying, Low temperature applications..

Also known as Refrigerated Incubator, Laboratory Cooled Incubator.

BICL-403 COOLED INCUBATOR



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Latest PID controller

R134a refrigerant, imported compressor

Independent temperature-limiting alarm system ensures experiments run safely.(Option)

Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature.(Option)

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

SPECIFICATIONS

Model	BICL-403
Capacity	250 L
Temperature Range	-40-65°C
Ambient Temperature	5°C ~ 35°C
Temperature Stability	High Temperature: $\pm 0.5^{\circ}\text{C}$, Low Temperature: $\pm 1.0^{\circ}\text{C}$
Display Resolution	0.1°C
Timer Range	0-9999 min
Internal Dimension	600Wx600Dx700H mm
Exterior Dimension	800Wx1160Dx1850H mm
Shelves	3
Power consumption	6100 W
Electrical Requirement	380V 50HZ



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com