



## NATURAL CONVECTION INCUBATOR BINC-7805

# NATURAL CONVECTION INCUBATOR BINC-7805

## BINC-7805 NATURAL CONVECTION INCUBATOR



P.I.D temperature controller provides accurate and reliable temperature control  
Natural convection heating allows the sample temperature to be uniform, suitable for sterilization, powder drying and high temperature storage  
Extended Life Silicone Rubber Gasket provides excellent sealing and long service life, but is easily replaced when the time for replacement is needed  
Volume(10L~210L)  
Inner chamber is made from corrosion-resistant mirror stainless steel  
Round curved inner angle is easy to clean  
Anti-skid shelf design, easy to operate by single hand  
Auto Start Feature after power loss/return  
Temperature deviation alarm  
Over current protection alarm  
Independent Over-temperature protection meets DIN 12880 International standard requirements provides you double protection

## SPECIFICATIONS

Model	BINC-7805
Capacity	210 L
Electrical requirement	220 V 50 Hz
Temperature Range	Amb +5 - 65°C
Display Resolution	0.1°C
Ambient Temperature	+5 - 35°C
Power Consumption	900 W
Inner glass door	Has
Viewing window	None
Interior Dimension	650Wx500Dx650H mm
Exterior Dimension	915Wx658Dx870H mm
Shelves	3 pcs



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)