



## LABORATORY REFRIGERATOR BLAR-410

## LABORATORY REFRIGERATOR BLAR-410

Laboratory refrigerators supplied with digital controller, glass door, alarm system to meet the demanding requirements of laboratory research. These refrigerator has temperature ranging from +2°C to +8°C and all models are combined with two exact sensors and auto defrost.

Used in Industry, Cosmetic, Pharmaceutical, Electronics, Laboratory, Medical, Research.

Also known as Laboratory Medical Refrigerator.

## BLAR-410 LABORATORY REFRIGERATOR

Foamed Door, Undercounter Mini type

### SPECIFICATIONS

Model	BLAR-410
Capacity	100 L
Temperature Range	2~8°C
Ambient Temperature	10~32°C
Refrigerant	R600a
Defrost Method	Auto Defrost
Controller	Microprocessor Control with digital Display
Control Sensor	NTC
Cooling Type	Forced air cooling
Shelf/drawer	Shelves/3
Alarms	High/low temperature, Power failure, Thermostat failure, Door ajar, Power failure backup system(alarm) 8h
Insulation	PURF
Material Inside	HIPS
Material Outside	Color sprayed steel
Noise Level	50 dB
Internal Size	385x356x737 mm
External Size	505x520x875 mm
Package Size	580x580x940 mm
CBM	0.32
20GP/40GP/40HQ	80/160/160
NT./GT. (kg)	30/33kg
Power consumption (kW.h/24h)	1.15
Power	80W
Current (A)	0.8A
Voltage/frequency (V/Hz)	220/50Hz
Standard Accessories	Foot, Castor, Outer door-foaming type, Door Lock, Test hole 25mm diameter, LED Lamp
Optional Accessory	Temperature recorder Datalogger



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)