



## GLOSS METER BMET-905

## GLOSS METER BMET-905

A glossmeter measures the specular reflection (gloss) of a surface. It determines the gloss by projecting a beam of light onto a surface at a fixed angle and intensity then measures the amount of reflected light at an opposite but equal angle.

## BMET-905 GLOSS METER



## SPECIFICATIONS

Model	BMET-905
Measuring Angle	60°
Measuring Area (mm)	60°:9X15
Measuring Range	60°:0~200 GU
Division Value	1 GU
Measuring Time	0.5 s
Repeatability	0~100GU:±0.5GU 100-200GU: ±0.5G U %
Accurate	second grade requirements of gloss meter
Auto Power-off Time	30 s
Language	Chinese English
Display	2.3 inch black and white screen
Size	160x52x84 mm
Weight	About 300 g
Power Supply	1 pc dry-cell battery(can measure 10000 times) or use USB Charge
Interface	USB
Operation Temperature Range	0~40 °C (32~104 °F)
Storage Temperature Range	- 20~50 °C (-4~122°F)
Humidity Range	< 85% RH, without condensation
Standard Accessories	User manual, calibration plate,USB cable, user manual, QC software (Download official website) calibration plate,user manual
Optional Accessories	Miniature printer



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada  
Email: [contact@biolabscientific.com](mailto:contact@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)