



DRYING OVEN BODR-303

DRYING OVEN BODR-303

With stainless steel interiors and fibreglass insulation between the walls to maximize thermal efficiency, hot air oven effectively sterilizes glassware, instruments and samples. Glass observation window eliminates the need of opening the door. Forced air convection system maintains temperature uniformity.

Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.

Also known as Heating Oven, Laboratory Drying Oven.

BODR-303 DRYING OVEN



Microcomputer PID intelligent temperature controller with LCD display

Air blower-heater and vertical hot air circulation system ensures temperature uniformity

Stainless steel inner chamber with cold rolling steel electrostatic spraying exterior

Semicircular arcs at corners for easy cleaning

Wide hollow tempered glass observation window

Adjustable air-tight buckle lock and silicone rubber seal ensures tight sealing and prevents heat loss

Easy to assemble and disassemble air duct lateral plate and bottom heater cover

Over temperature protection and Timer function

SPECIFICATIONS

Model	BODR-303
Capacity	65 L
Temperature Range	RT+10-300°C
Ambient Temperature	5-40°C
Temperature Accuracy	±1°C
Temperature Uniformity	±2°C(at 100°C), ±3.5°C(at 200°C)
Temperature Resolution	±0.1°C
Timer Range	1-9999 min
Internal Dimension	400Wx360Dx450H mm
Exterior Dimension	540Wx540Dx830H mm
Package Size	650x640x920 mm
Shelves	2
Weight	44/54 kg
Power	1600 W
Power Supply	220V, 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com