PRODUCT CATALOG

DRYING OVEN BODR-305

ISO9001 CERTIFIED

www.biolabscientific.com

DRYING OVEN BODR-305

With stainless steel interiors and fibreglass insulation between the walls to maximize thermal efficiency, hot air oven effectively sterilizes glassware, instruments and samples. Glass observation window eliminates the need of opening the door. Forced air convection system maintains temperature uniformity.
Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.
Also known as Heating Oven, Laboratory Drying Oven.

BODR-305 DRYING OVEN

- Microcomputer PID intelligent temperature controller with LCD display
- Air blower-heater and vertical hot air circulation system ensures temperature uniformity
- Stainless steel inner chamber with cold rolling steel electrostatic spraying exterior
- Semicircular arcs at corners for easy cleaning
- Wide hollow tempered glass observation window
- Adjustable air-tight buckle lock and silicone rubber seal ensures tight sealing and prevents heat loss
- Easy to assemble and disassemble air duct lateral plate and bottom heater cover
- Over temperature protection and Timer function

SPECIFICATIONS

Model	BODR-305
Capacity	230 L
Temperature Range	RT+10-300°C
Ambient Temperature	5-40°C
Temperature Accuracy	±1°C
Temperature Uniformity	±4°Cat 180°C
Temperature Resolution	±0.1°C
Timer Range	1-9999 min
Internal Dimension	600Wx500Dx750H mm
Exterior Dimension	730Wx670Dx1220H mm
Package Size	900x790x1365 mm
Shelves	2
Weight	94/120 kg
Power	3000 W
Power Supply	220V, 50Hz

Biolab Scientific Ltd.
3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com