



## DRYING OVEN BODR-402

## DRYING OVEN BODR-402

With stainless steel interiors and fibreglass insulation between the walls to maximize thermal efficiency, hot air oven effectively sterilizes glassware, instruments and samples. Glass observation window eliminates the need of opening the door. Forced air convection system maintains temperature uniformity.

Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.

Also known as Heating Oven, Laboratory Drying Oven.

## BODR-402 DRYING OVEN



304 stainless steel, mirror polishing processing, semicircular arcs at corners easy to clean and maintain. The space between the shelves in the chamber is adjustable  
PID controller with over temperature alarm and Timer function ensures precise and reliable control

Ceramic fiber door seal, which can run at high temperature for a long time and has a long service life

Programmable controller: 7 periods 63 steps, 0 ~5999mins for each period, can preset boot and shutdown time, adjustable circulating fan

Independent over-temperature alarm system ensures experiments running safely

## SPECIFICATIONS

Model	BODR-402
Capacity	100 L
Temperature Range	RT+20°C- 500°C
Ambient Temperature	5-40°C
Temperature Stability	±0.5°C
Display Resolution	0.1°C
Timer Range	0~5999 min
Internal Dimension	450Wx450Dx450H mm
Exterior Dimension	990Wx790Dx990H mm
Shelves	2
Power Consumption	4900 W
Electrical Requirement	AC380 V 50 Hz



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada  
Email: [contact@biolabscientific.com](mailto:contact@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)