



FORCED CONVECTION OVEN BOFC-102

FORCED CONVECTION OVEN BOFC-102

Vertical air circulation system produces faster temperature response rates and ensures temperature uniformity. Microprocessor PID controls deliver fast ramping rate and ensures stability during the operation.

Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.

Also known as Oven, Laboratory Forced Convection Oven.

BOFC-102 FORCED CONVECTION OVEN



Microcomputer PID intelligent temperature controller with LCD display

Air blower-heater and vertical hot air circulation system ensures temperature uniformity

Stainless steel inner chamber with cold rolling steel electrostatic spraying exterior

Adjustable air-tight buckle lock and silicone rubber seal ensures tight sealing and prevents heat loss

Semicircular arcs at corners for easy cleaning

Wide hollow tempered glass observation window

Easy to assemble and disassemble air duct lateral plate and bottom heater cover

Independent temperature safety device

Over temperature protection and Timer function

SPECIFICATIONS

Model	BOFC-102
Capacity	45 L
Temperature Range	RT+5-300°C
Ambient Temperature	5-40°C
Temperature Accuracy	±1°C
Temperature Uniformity	±2.0°C
Temperature Resolution	±0.1°C
Timer Range	1-9999 min
Load per shelf	15 kg
Internal Dimension	350Wx350Dx350H mm
Exterior Dimension	490Wx530Dx730H mm
Package Size	630x600x820 mm
Shelves	2
Weight	37/45 kg
Power	1200 W
Power Supply	220V, 60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com