





GENERAL PURPOSE OVEN BOGP-303





GENERAL PURPOSE OVEN BOGP-303

Designed for continuous drying operations, general purpose ovens provide temperature homogeneity regulated by microcomputer control system. Stainless steel interiors with easy to clean surface while silicon rubber sealing prevents heat loss and gives stability during operation.

Used in Drying, Roasting, Laboratory, Research, Engineering, Industry, Agricultural, Biology. Also known as Laboratory Oven, Laboratory general Purpose Oven.

BOGP-303 GENERAL PURPOSE OVEN



Micro-computer intelligent PID control system with LCD display

Forced air convection maintains temperature uniformity

Stainless steel inner chamber and cold rolling steel electrostatic spraying exterior

Easy to clean semicircular corners with adjustable shelves

 $\label{lock} \mbox{Door with wide double-glass observation window and adjustable air-tight buckle lock}$

Silicon rubber sealing ring prevents heat loss

Two independent temperature safety device, auto alarm and heating suspension incase of failure of main controller

Automatic switch-off timer

Can be connected to printer

SPECIFICATIONS

Model	BOGP-303
Capacity	65 L
Temperature Range	RT+10-300°C
Temperature Accuracy	±1°C
Temperature Uniformity	±2.0°C
Temperature Resolution	±0.1°C
Timer Range	1-9999 min
Internal Dimension	400Wx360Dx450H mm
Exterior Dimension	550Wx550Dx840H mm
Package Size	650x640x920 mm
Shelves	2
Weight	44/54 kg
Power	1600 W
Power Supply	220V/110V, 60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada Email: contact@biolabscientific.com | Website: www.biolabscientific.com