



GENERAL PURPOSE OVEN BOGP-304

GENERAL PURPOSE OVEN BOGP-304

Designed for continuous drying operations, general purpose ovens provide temperature homogeneity regulated by microcomputer control system. Stainless steel interiors with easy to clean surface while silicon rubber sealing prevents heat loss and gives stability during operation.

Used in Drying, Roasting, Laboratory, Research, Engineering, Industry, Agricultural, Biology.

Also known as Laboratory Oven, Laboratory general Purpose Oven.

BOGP-304 GENERAL PURPOSE OVEN



- Micro-computer intelligent PID control system with LCD display
- Forced air convection maintains temperature uniformity
- Stainless steel inner chamber and cold rolling steel electrostatic spraying exterior
- Easy to clean semicircular corners with adjustable shelves
- Door with wide double-glass observation window and adjustable air-tight buckle lock
- Silicon rubber sealing ring prevents heat loss
- Two independent temperature safety device, auto alarm and heating suspension incase of failure of main controller
- Automatic switch-off timer
- Can be connected to printer

SPECIFICATIONS

Model	BOGP-304
Capacity	125 L
Temperature Range	RT+10-300°C
Temperature Accuracy	±1°C
Temperature Uniformity	±2.0°C
Temperature Resolution	±0.1°C
Timer Range	1-9999 min
Internal Dimension	500Wx450Dx550H mm
Exterior Dimension	636Wx680Dx915H mm
Package Size	750x730x1020 mm
Shelves	2
Weight	60/72 kg
Power	2300 W
Power Supply	220V, 60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com