



HIGH PERFORMANCE OVEN BOHP-106

HIGH PERFORMANCE OVEN BOHP-106

This range of ovens feature high quality construction and efficient insulation to provide superior degree of temperature uniformity. Over heat and short circuit protection makes it ideal for high temperature applications.

Used in Drying, Roasting, Laboratory, Research, Engineering, Industry, Agricultural, Biology.

Also known as Laboratory Oven, Laboratory High Performance Oven.

BOHP-106 HIGH PERFORMANCE OVEN

Microprocessor Digital controller

Forced air convection maintains temperature uniformity

High quality cold rolled steel sheet exterior and stainless steel SUS304 inner chamber

Silicon rubber sealing ring prevents heat loss

Heat insulating material: PU FOAM + Glass fiber cotton

Non-condensation observation window with light

Temperature Sensor: PT100

Noise level: ≤ 65 dB

Over-load, over heat, over-current and short-circuit protection

SPECIFICATIONS

Model	BOHP-106
Capacity	640 L
Temperature Range	RT+10-300°C
Temperature Accuracy	$\pm 1^{\circ}\text{C}$
Temperature Fluctuation	$\pm 0.5^{\circ}\text{C}$
Temperature Uniformity	$\pm 2^{\circ}\text{C}$ (at 100°C), $\pm 3.5^{\circ}\text{C}$ (at 200°C)
Temperature Resolution	$\pm 0.1^{\circ}\text{C}$
Heating Rate	2.0-3.0°C/min
Cooling Rate	1.0-2.0°C/min
Timer Range	1-9999 min
Internal Dimension	800Wx800Dx1000H mm
Exterior Dimension	980Wx1030Dx1310H mm
Shelves	2
Noise Level	≤ 65 dB
Weight	173/198 kg
Power	5000 W
Power Supply	120V/220V/240V/380V/415V, 50Hz/60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com