



INTEGRATED OR LAMP BOPL-304

INTEGRATED OR LAMP BOPL-304

Shadowless operation lamp is suitable for the requirement of various operation conditions and it is ideal operating lighting equipment for modern operation rooms. Based on trichromatic theory, the light is closer to natural light, which is suitable for medical workers to distinguish the color of vascular tissue, nerve ending and so on. Adapts US blue cold light coating technology, the optical filter could effectively filter ultraviolet rays from the spectrum.

Used in Medical unit, Surgery, Operation theatre.

Also known as Integrated surgical Light, Integrated OT light.

BOPL-304 INTEGRATED OR LAMP



The imported switch power supply is adopted to control the voltage, making the work voltage permanently stable

The removable handle sheath can be disinfected at the high temperature of 135°C

The special radiation filter reducing the heat to the minimum level

The depolished panel is made of imported material makes the light rays softer

The multi-flake retroreflector made of imported aluminum sheet, has the feature of no coating film and never fading

Light adjustment circuit adopts CPU control, enabling increase or decrease of illumination and boasting brightness memory

One lamp holder with two bulbs enables automatic operation of the standby bulb in 1/2 second when the main bulb malfunctions, and it has indicators for damage of main or standby bulb

Imported lamp receptable, Tungsten halogen bulbs of international brand are adopted with average service more than 1500 hrs.

AC/DC, may satisfy when the power failure continues the surgery. (AC / DC type)

SPECIFICATIONS

Model	BOPL-304
Illumination	80,000-140,000/80,000-140,000 LUX (at 1m distance)
Color temperature	4500K±500K
Color rendering Index	100≥Ra≥85
Diameter of lamp holder	600/600 mm
Shift of major and stand by lamps	automatic
Depth of light beam	≥700cm
The Value of total irradiance	<6 mW/m ² lx
Total irradiance	<600 W/m ²
Brightness adjustment	CPU light- dimmer
Maximum Height for installation	2800-3200 mm
Light field diameter	10-28 cm at 1m
Bulb Power	150W 24V Bulb power
Input power	440+10% VA
Power Supply	220V±10% 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com