



VACUUM OVEN BOVA-302

VACUUM OVEN BOVA-302

With quick heating times and and high precision temperature control, vacuum ovens effectively handle heat and oxygen sensitive materials with unmatched gentleness while drying. Designed to operate with reduced pressures, it ensures quick and effective drying of samples in powder or pellet form.

Used in Biochemical, Pharmaceutical, Healthcare, Agricultural, Environmental protection, disinfection, Sterilization, Drying, Roasting, Laboratory, Research, engineering, Industry,.

Also known as Vacuum Oven, Laboratory Vacuum Oven.

BOVA-302 VACUUM OVEN



Microcomputer PID temperature controller with function of timer function

Stainless steel inner chamber with cold rolling steel electrostatic spraying exterior

Double-layer tempered glass anti-bullet door with high permissibility

Over-temperature protection

SPECIFICATIONS

Model	BOVA-302
Capacity	52.2 L
Temperature Range	RT+10-250°C
Temperature Accuracy	±1°C
Temperature Uniformity	±2.0°C
Temperature Resolution	±0.1°C
Vacuum Degree	< 133 Pa
Timer Range	1-9999 min
Internal Dimension	415Wx370Dx340H mm
Exterior Dimension	560Wx540Dx680H mm
Package Size	720x680x780 mm
Shelves	2
Weight	67/92 kg
Power	1400 W
Power Supply	220V, 60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com