



VACUUM OVEN BOVA-7506

VACUUM OVEN BOVA-7506

BOVA-7506 VACUUM OVEN



- Programmable vacuum cycle
- LCD vacuum degree window
- Suitable for drying thermo-sensitive material
- Shorter drying time for sample that does not dry easily
- Dual layer tempered glass door for clear observation
- Fully automatic electromagnetism controlled vacuum
- Minimum heating time 50% less than traditional vacuum oven

SPECIFICATIONS

Model	BOVA-7506
Capacity	64 L
Electrical requirement	AC 220 50 HZ
Temperature Range	RT+10 - 200°C
Display Resolution	0.1°C
Temperature Stability	±1°C
Vacuum Gauge	Digital Display
Vacuum Degree	133 Pa
Vacuum Sensor	Resistance silicon tube pressure sensor
Vacuum Control Range	10 - 100000 Pa
Power Consumption	1800 W
Interior Dimension	400Wx400Dx400H mm
Exterior Dimension	600Wx570Dx1390H mm
Shelves	3 pcs
Chamber Material	304 Stainless steel



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com