



VARIABLE VOLUME SINGLE CHANNEL  
MICROPIPETTE BPIP-522

## VARIABLE VOLUME SINGLE CHANNEL MICROPIPETTE BPIP-522

Single Channel Pipette is the new standard for microliter measurements. It is top of the line micropipette that is ergonomically designed and easily adjustable. They are commonly used in laboratory, research, chemistry, biology, forensic, pharmaceutical, and drug discovery labs to transfer small quantities of liquid.

Used in Environmental Sciences, Laboratory, Research, Liquid Handling Task, Institutes, Pharmaceutical, Industrial, Microbiology, Chemistry, Biology, Medical, Plasmid Purification.

Also known as Micropipette, Laboratory Single Channel Pipette, Laboratory Micropipette.

## BPIP-522 VARIABLE VOLUME SINGLE CHANNEL MICROPIPETTE



- Large central pipetting button and separate ejection function
- True one-handed operation for both right-and left-handers
- Completely autoclavable at 121°C(20min)
- Volume-change protection
- 4-Position volume display, always clearly visible externally
- Short stroke of only 12.5mm to reduce the risk of RSI (Repetitive Strain Injury)
- Corrosion-resistant piston and ejector
- Color-coded for easy selection of the right tip

## SPECIFICATIONS

Model	BPIP-522
Autoclavable	121°C
Volume	0.5-10 µl
Increment (µl)	0.01
Accuracy* $\pm\%$	1
CV* $\leq\%$	0.5
Unit	20



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada  
Email: [contact@biolabscientific.com](mailto:contact@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)