



Product Image Coming Soon


# LOW TEMPERATURE KINEMATIC VISCOMETER BPTL-102

## LOW TEMPERATURE KINEMATIC VISCOMETER BPTL-102

Viscosity of an oil is defined as its resistance to flow and Viscometer measures the flow. Monitoring viscosity is one of the most important components of any oil analysis program. Minute changes in viscosity at operating temperatures can be magnified to the extent that an oil is no longer able to provide adequate lubrication and efficiency in preventing friction between moving parts.

Used in Petroleum Industry, Oil and Gas Industry.

### BPTL-102 LOW TEMPERATURE KINEMATIC VISCOMETER



Product Image Coming Soon

2 working units, Dewar low temperature bath with lighting. Safety protection device can prevent over-low liquid level.

## SPECIFICATIONS

Model	BPTL-102
Working units	2
Temperature controlling range	50 - 40 °C ± 0.1 °C
Refrigerated by	Shock absorption air compressor, Fluorine free
Safety	Device can prevent over-low liquid level



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)