



## MINI ROTARY VISCOMETER BPTL-103

## MINI ROTARY VISCOMETER BPTL-103

Viscosity of an oil is defined as its resistance to flow and Viscometer measures the flow. Monitoring viscosity is one of the most important components of any oil analysis program. Minute changes in viscosity at operating temperatures can be magnified to the extent that an oil is no longer able to provide adequate lubrication and efficiency in preventing friction between moving parts.

Used in Petroleum Industry, Oil and Gas Industry.

## BPTL-103 MINI ROTARY VISCOMETER



Automatic nonlinear curve temperature control, can be edited and drawn in real-time according to requirements. Calculate and print borderline pumping temperature of Gas barrier type and flow limited type; Equipped with newly developed defrost system.

## SPECIFICATIONS

Model	BPTL-103
Temperature range	- 5 °C - 40 °C ± 0.02 °C
Temperature control	Automatic nonlinear curve
Window operation system	XP, Win7
Optional accessory	Test components of ASTM D6896 and ASTM D6821



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada  
Email: [contact@biolabscientific.com](mailto:contact@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)