



# AUTOMATIC CAPILLARY VISCOMETER WASHER BPTL-108

## AUTOMATIC CAPILLARY VISCOMETER WASHER BPTL-108

Viscosity of an oil is defined as its resistance to flow and Viscometer measures the flow. Monitoring viscosity is one of the most important components of any oil analysis program. Minute changes in viscosity at operating temperatures can be magnified to the extent that an oil is no longer able to provide adequate lubrication and efficiency in preventing friction between moving parts.

Used in Petroleum Industry, Oil and Gas Industry.

## BPTL-108 AUTOMATIC CAPILLARY VISCOMETER WASHER



It adopts micro-controller control technology, program control, automatic washing. It needs less solvent oil and it is convenient, efficient. It can be widely used in the enterprises producing and using petroleum products, colleges and universities, and scientific research institutes and so on, where capillary viscometer are used. High degree automation.

## SPECIFICATIONS

Model	BPTL-108
Water bath temperature control range	Ambient to 80 °C
Ambient temperature	15 °C ~ 35 °C
Relative humidity	≤ 85 %
Maximum power consumption	700 W
Power supply	AC (220 ± 10%) V, 50 Hz
Dimension	320×300×500 mm (excluding the aspirator )
Net weight	24kg (excluding the aspirator)



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)