



Product Image Coming Soon

FOAMING TENDENCY TESTER BPTL-219

FOAMING TENDENCY TESTER BPTL-219

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-219 FOAMING TENDENCY TESTER



Product Image Coming Soon

Special holding device can prevent cylinder floating upward very well, press block is unnecessary. Air filter, with molecular sieve. Electronic flow meter controls flow at 1000 ± 5 ml/min (optional)

SPECIFICATIONS

Model	BPTL-219
Units	Main unit and gas source controller
Flow meter	Electronic, controls flow at 1000 ± 5 ml/min (optional)
Air filter	With molecular sieve
Holding device	Special holding device, can prevent cylinder floating upward very well press block is unnecessary.
Structure	360° complete transparent structure, easy to observe
Stirrer	Sputtering turbine stirrer guarantees temperature uniformity
Safety device	Avoids over-heating or low liquid level
Operation	Touch screen
Optional	Segment timing foam volume with buzzer prompt.



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com