



AUTOMATIC COC FLASH POINT TESTER BPTL-234

AUTOMATIC COC FLASH POINT TESTER BPTL-234

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-234 AUTOMATIC COC FLASH POINT TESTER



The instrument adopts LCD screen to display. It is applicable to all petroleum products with flash points above 79°C and below 400°C except fuel oils. Differential coefficient detection. Automatically correct the system deviation.

SPECIFICATIONS

Model	BPTL-234
Mode	Electric ignition
Ignition mode	
Gas flame diameter	3.2 mm~4.8 mm
Flash point determination	
Range	Ambient to 400°C
Repeatability	≤ 8°C (Flash Point)
Reproducibility	≤ 17 °C (Flash Point)
Ambient temperature	(10~40) °C
Power supply	AC (220±10%) V, 50Hz
Maximum power consumption	500 W
Dimension	460×430×290 mm
Net weight	22.5 kg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com