



**Product Image Coming Soon**

## LOW-TEMPERATURE TESTER BPTL-254

## LOW-TEMPERATURE TESTER BPTL-254

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

Also known as Solidifying Point Tester.

## BPTL-254 LOW-TEMPERATURE TESTER



Product Image Coming Soon

The instrument is newly designed and is suitable to determine solidifying point of petroleum products. It is widely used in oil exploitation companies, petroleum manufacturers, petroleum users, colleges and scientific research institutes. The material of workbench is stainless steel. It adopts special technology. It is no need to use cooling liquid in cold chamber. The cooling rate is fast and efficiency is high. The instrument adopts bench structure. The design is simple and easy to use.

## SPECIFICATIONS

Model	BPTL-254
Working chamber	Two test baths in one chamber. The temperatures are the same.
Temperature controller	
Range	Ambient to -70°C
Accuracy	±0.5°C
Refrigeration	New-type refrigeration compressor
Ambient temperature	≤30°C
Relative humidity	≤ 85%
Maximum power consumption	1000W
Power supply	AC(220±10%)V, 50Hz
Dimension	620×460×340 mm
Net weight	50 kg



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada  
Email: [contact@biolabscientific.com](mailto:contact@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)