



FOAMING CHARACTERISTICS TESTER BPTL-262

FOAMING CHARACTERISTICS TESTER BPTL-262

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-262 FOAMING CHARACTERISTICS TESTER



The instrument is used to determine the foaming tendency and stability of lubricating oils. The instrument adopts all-in-one structure. It includes three parts: low temperature test part and its control, high temperature test part and its control, a portable cooler for low temperature test part. The instrument equips an automatic timing alarm.

SPECIFICATIONS

| Model | BPTL-262 |
|---|------------------------------------|
| Temperature control range for high temperature bath | (Room temp.~99.9)°C |
| Temperature control range for low temperature bath | (5~99.9)°C |
| Temperature control accuracy | ±0.5°C |
| Air flow rate | (94±5)ml/min,adjustable |
| Timer | 5min and 10min, accurate to second |
| Ambient temperature | 15°C~35°C |
| Relative humidity | ≤ 85% |
| Total power consumption | ≤2700W |
| Power supply | AC(220±10%)V, 50Hz |
| Dimension | |
| Main unit | 690×460×700 mm |
| Cooler | 400×450×300 mm |
| Net weight | 48 kg |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com