



Product Image Coming Soon

DROPPING POINT TESTER (OIL BATH) BPTL-270

DROPPING POINT TESTER (OIL BATH) BPTL-270

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-270 DROPPING POINT TESTER (OIL BATH)



Product Image Coming Soon

The oil bath is composed of heat resistant beaker, heater and electric motor. The heating power can be adjusted continuously. The temperature in oil bath is uniform. Desktop structure. Easy to operate

SPECIFICATIONS

Model	BPTL-270
Oil Bath	600ml Beaker
Grease Cup	It is made of chrome plated brass, inner diameter: 9.92mm, oil dripping hole:2.8mm, cup height: 12mm
Test Tube	Heat resistant borosilicate glass tube with edge, inner diameter: 11.1 mm to 12.7 mm, and there are three grooves on the circumference 19 mm away from the bottom to support the grease cup
Stirring motor	60 R / min
Working environment: Temperature	(- 5 ~ 300) °C
Relative humidity	≤ 85%
Total power consumption	≤900W
Power supply	AC(220±10%)V, 50Hz
Dimension	350×180×410 mm
Net weight	8 kg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com