

INCUBATOR SHAKER BSBT-401


INCUBATOR SHAKER BSBT-401

Bench top shaking incubator has a compact design that saves your precious lab space. Stainless steel interiors with exceptional durability and trouble-free cleaning require less maintenance. Large transparent lid provides easy observation. Microprocessor controller permits easy operation. A variety of platforms and other lab accessories allows configuration to meet your demands.

Used in Cell Cultures, Cell Aeration, Microbiology, Increasing Solubility Rates, Metabolism Studies, Bacterial Cultures, Bacteriology.

Also known as Laboratory Incubator Shaker, Incubator Shaker.

BSBT-401 INCUBATOR SHAKER



PID speed control technology.

Integrate incubator and shaker. Save lab space.

Compact constant temperature space, good temperature uniformity, low noise.

Micro-processor controls temperature and shaking speed. Built-in timing function.

Sound alarms after program finishes, it can also be set to untimed continuous operation.

Brushless DC motor, long life and maintenance-free.

SPECIFICATIONS

| | |
|------------------------|----------------------------------|
| Model | BSBT-401 |
| Speed Range | 50 ~300 rpm |
| Temp. control range | 4 ~60°C @Ambient temp.≤25°C |
| Temp. setting range | 4 ~60°C |
| Shaking Orbit | 20 mm (circle) |
| Max. drop temp. | R.T. decrease 20°C@R.T.≥25°C |
| Temp. stability | ±0.3°C |
| Temp. Display accuracy | 0.1°C |
| Timing range | 1min ~99h59min |
| Voltage | AC 220V , 50/60Hz |
| Power | 1200W |
| Fuse | 250 V, 5 A/10 A, φ5x20 |
| Dimension | W.560xD.823xH.449 |
| Net weight | 61 Kgs |
| Platform | PW-420 (W.410 x D.420 x H.65 mm) |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com