



COOLED SHAKING INCUBATOR BSCO-203

COOLED SHAKING INCUBATOR BSCO-203

Equipped with precise cooling system and superior quality, low noise centrifugal fan that provides outstanding temperature uniformity ideal for most low temperature applications. Energy efficient, easy to clean design is an advantage for maximum process stability during microbiological tasks.

Used in Cell Culturing, Cell Aeration, Solubility Studies, Sample Preparation, Water Analysis, BOD Measurement, Plating, Breeding Experiments, Research Institutions, Universities, Colleges.

Also known as Cooled Shaking Incubator, Shaker Incubator, Laboratory Cooled Shaking Incubator.

BSCO-203 COOLED SHAKING INCUBATOR



Microprocessor controller
Stainless steel interior and Electrostatic sprayed exterior
LCD display

SPECIFICATIONS

Model	BSCO-203
Speed Range	20-300 rpm
Standard Capacity	2000 mlx8
Temperature	4°C~60°C
Temperature Accuracy	±0.1°C
Temperature Uniformity	±1°C
Shaking Speed Accuracy	±1 rpm
Timing Range	Optional
Motion	Orbital
Amplitude	26 mm
Tray	1
Platform Dimension	920x500 mm
Overall Dimension	1100x765x890 mm
Display	LCD
Weight	183 kg
Power	1800 W
Power Supply	220 V, 60 Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com