



**DOUBLE BEAM UV VISIBLE
SPECTROPHOTOMETER BSDBU-203-A**

DOUBLE BEAM UV VISIBLE SPECTROPHOTOMETER BSDBU-203-A

Designed to conserve benchspace, our product offers the measurement range of 190-1100nm at bandwidth of 1.8nm and 2nm. Engineered for a wide range of applications, our systems provide dependable performance and reliable results. It produces the photometric range of -0.3 to 3 A; 0-200 %T and photometric accuracy of $\pm 0.2\%T$ which makes it suitable for various quantitative assays.

BSDBU-203-A DOUBLE BEAM UV VISIBLE SPECTROPHOTOMETER



Unique Long light path design

520mm long light path greatly improved the wavelength resolution

Advanced Stand-alone System with Multi Functions

Spectrum scanning, Standard curve, Kinetics, Multi wavelength, DNA/Protein test can be operated

directly on device and all corresponding curves and data can be displayed directly

Rigid Structure, 16mm-thick Optical Base

All optical components are fixed on a 16mm thick rigid die-cast aluminum board to promise higher stability and reliability

One-button Automatic Calibration System

One button auto calibration for baseline, wavelength and dark current to keep device in a good condition

6 inches High-Definition Large LCD Display

Large LCD display, all data and graphs can be shown directly and clearly

Easy Data Output by USB/Parallel Port

USB Port: Connect to computer and operate through PC software (PC software is standard)

Parallel Port: Connect to micro thermal printer to print test data(Micro thermal printer is optional)

Powerful Software Functions

Spectrum scanning, Standard curves, Kinetics, Multi wavelength scanning, DNA/Protein test can be operated directly on computer

SPECIFICATIONS

Model	BSDBU-203-A
Wavelength Range	190-1100 nm
Wavelength Accuracy	± 0.1 nm at 656.1 nm, ± 0.3 nm at all range
Wavelength Repeatability	≤ 0.1 nm
Spectral Bandwidth	1.8 nm
Photometric Range	-0.3-3 A, 0-200% T, 0-999 C
Photometric Accuracy	$\pm 0.3\%$ T (0-100% T)
Photometric Repeatability	$\leq 0.1\%$ T (0-100% T)
Stability	≤ 0.001 A/30 min at 500 nm
Stray Light	$\leq 0.05\%T$ at 220 nm & 360 nm
Output	USB port & Parallel Port
Display	320*240 Dots LCD
Light Source	W Lamp & D2 Lamp

Detector	Silicon Photodiode
Power Requirements	AC110/220 V, 50/60 Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com