



FLUORESCENCE SPECTROPHOTOMETER BSFL-103

FLUORESCENCE SPECTROPHOTOMETER BSFL-103

Biolab Fluorescence spectrophotometers incorporate excellent wavelength accuracy and highly reliable optical performance to give highest sensitivity, reproducibility and accuracy. Xenon lamp minimizes photobleaching of samples thus maintaining sample integrity and produces high signal to noise ratio to give unmatched performance even with trace samples. Ergonomic with a longer lamp life, it gives more quality for your money.

Used in It serves a wide range of demanding clinical research, molecular biology, pharmaceutical and industrial applications..

BSFL-103 FLUORESCENCE SPECTROPHOTOMETER



Wavelength range: 250-700 nm

Sensitivity: S/N \geq 150

Wavelength accuracy: \pm 1nm at spectral bandwidth of 10nm

Unparalleled detection Limit: With 150 Watts Xenon lamp, it offer higher signal to noise ratio, which provide better capabilities for trace sample measurement.

Highly reliable optical performance: The 1200 lines/mm Czerny Turner Diffraction Grating for the highest sensitivity, accuracy and reproducibility

Easy software Interface: Data Collection and Analysis software offers a comprehensive solution for data collection and analysis such as scan, time drive, and ratio Data Collection directly from the applications menu. Outstanding durability and reliability

Drastically reduced photobleaching of samples: Unlike conventional light sources, the improved Xenon lamp minimizes photobleaching of samples, which maintains the integrity of the sample; hence delivers accurate and uncompromised results.

RS232 interface

It gives you the low cost of ownership by offering an exceptionally long lifetime of 2.8 billion flashes and the lamp typically will be remain active up to next 10 years which will save your money.

Eight stage adjustable sensitivity, real time display of fluorescence reading with concentration printout

Standard Accessories: Power cord, fuse, 10mm quartz fluorescence cuvette

SPECIFICATIONS

Model	BSFL-103
Wavelength Accuracy	\pm 1 nm
Wavelength Repeatability	\leq 0.5 nm
Spectral Bandwidth	10 nm
Stability	Better than 1.5% per 10 min
Light Source	Xenon Lamp
Excitation Optical Filter	Interference optional filter of central wavelength at 365nm, optional interference filter of 25mm diameter of wavelength range 250-700nm
Excitation Wavelength Range	250-700 nm
Emission Wavelength Range	200-900 nm
Linearity	R \geq 0.995
Response Time	0.1-4 sec
Monochromator	Czerny Turner Diffraction Grating
Gross Dimension (W/D/H)	380x440x240 mm
Weight (Net/Gross)	14 kg
Power	190 W

Power Supply	220V±22V, 50Hz±1Hz
--------------	--------------------



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com